

Silencer® 910 Specifications

AC INPUT	
Operating Range:	90-264 VAC .98 power factor
Frequency:	47-63Hz
Current:	15A
Efficiency:	88% Typical Load (80+ Silver)
EMI:	FCC-B, CE
DC OUTPUT	
Output:	+5V @ 30A +12V@ 74A (82A peak) -12V @ 0.8A +3.3V @ 24A +5VSB @ 3A continuous power = 910W peak power = 1000W
Regulation:	2% (+3.3V, +5V, +12V) 5% (-12V)
Ripple:	1% (p-p)
Hold Time:	>24ms
PG Delay:	300ms
SAFETY	
OV Protection:	+3.3V, +5V, +12V
OC Protection:	135% OPP
Agency Approval:	UL/cUL/CE/CB/TUV/RoHS
ENVIRONMENTAL	
Temperature:	0° - 50°C
Humidity:	20% - 80% RH
Fan Type:	25 - 50 CFM ball-bearing
Noise:	26 - 41 dB(A)
MISCELLANEOUS	
Compatibility:	NVIDIA® SLI™ Certified, EPS12V
M/B Connectors:	24-pin, 8-pin CPU, 4/8-pin CPU
Graphic Connectors:	Two 6-pin and two 6/8-pin PCI-E
Drive Connectors:	12 SATA, 7 Peripheral, 1 Floppy
MTBF:	100,000 hrs
Power Cord:	6' 14AWG (incl.)
Warranty:	5 Years



www.pcpowercooling.com • 5995 Avenida Encinas, Carlsbad, CA 92008 • (760) 931-5700 • (800) 722-6555

Reviews, specifications, and pricing available on website. NVIDIA and SLI are registered trademarks and trademarks of NVIDIA Corporation. Turbo-Cool and PC Power and Cooling are registered trademarks of PC Power & Cooling, Inc. ©2007